

CHANDLER “NURSE RITE” AUGER TENDERS

- Skid mounted platform models or trailer mounted models in either size.
- Fixed rear discharge auger or side folding discharge auger— your choice at NO cost difference on either size.
- Large 8” diameter auger tube for discharging capacities up to 1500 pounds per minute. Auger, tube and core manufactured of 304 stainless steel.
- Unitized one piece (solid welded) hopper.



5 Ton



8 Ton



5 Ton

- Hopper Mfd. of 304 stainless steel only—single compartment
- 170 cubic ft. capacity struck level
- Axles: tandem, Henschen (Rubber Flex) 13,000# capacity
- 12.5L rib implement tires
- 10 H.P. motor w/starter (less battery)
- Standard Auger has 96" discharge height
- Overall height 110"
- Overall width 94"

"Optional Equipment"

- Hydraulic motor to run off tractor hook up
- 16 H.P. motor with self contained hydraulic system
- Fitted tarp and bow
- Flexible discharge hose
- Highway tires and wheels
- Surge brake system:
Single or tandem axles
- Extra auger lengths
- Ladder



8 Ton

- Hopper Mfd. of 304 or 409 stainless steel—two compartments
- 265 cubic ft. capacity struck level
- Axles: Tandem, Henschen (Rubber Flex) 20,000# capacity
- 16.5L Rib implement tires
- 20 H.P. motor with self-contained hydraulic system (less battery)
- Standard Auger has 118" discharge height
- Overall height 126"
- Overall width 96"

"Optional Equipment"

- Hydraulic motor to run off tractor hook up
- 10 H.P. motor w/starter (less battery)
- Fitted tarp and bow
- Flexible discharge hose
- Highway tires and wheels
- Surge brake system:
Single or tandem axles
- Catwalks
- Ladder